



## SPIN

VERSATILE BAGGER MACHINE  
from 0° to 30°

Model	Reel-holder width	sealing jaws width	Bag dimensions
Modello	Larghezza portabobina	Lunghezza spatole saldanti	Dimensioni sacchetto
Spin	700mm	340 mm	300mm largh. /width x 180mm alt. /height

### **Versatile rotary packing machine from 0° (horizontal) to 30° (inclined)**

Technical characteristics of the machine:

- Machine structure in painted steel, parts in contact with the product in stainless steel.
- Maximum film reel width 700 mm, outer diameter of the reel max 300 mm.
- Adjustable forming tunnel.
- Manual rotation of the machine with hand wheel.
- Cross-cut sealing group with jaw width of 340 mm.
- Group of longitudinal sealing wheels with:
  - a pair of wheels to pull the film,
  - a pair of heat-sealing wheels,
  - a pair of folding wheels.
- Exit slide.
- Safety guards with safety sensors.
- Photoeye for bag length.
- Electrical panel with touch screen control panel, does not require compressed air.
- Compatible films: heat-sealable such as polypropylene, polythene, micro-perforated, laminated etc.

SPEED: UP TO 30 BAGS PER MINUTE (depends on the product and type of film used)

#### **MACHINE DIMENSIONS**

Width: 1200 mm

Length: 1600 mm

Height: 1300 mm



### **Macchina confezionatrice rotativa dai 0° (orizzontale) a 30° (inclinata)**

#### **Caratteristiche tecniche della macchina:**

- *Struttura della macchina in Acciaio verniciato, parti a contatto con il prodotto in Acciaio Inox.*
- *Porta bobina Fascia max 700 mm, diametro esterno bobina max 300 mm.*
- *Tunnel conformatore sacchetto regolabile.*
- *Rotazione manuale della macchina con volantino.*
- *Gruppo Taglia-Salda trasversale con larghezza standard delle ganasce di 340 mm.*
- *Gruppo Ruote di saldatura longitudinale con:*
  - *una coppia di ruote per il traino,*
  - *una coppia di ruote termosaldanti,*
  - *una coppia di ruote Piegalemba.*
- *Scivolo in uscita*
- *Carterature antinfortunistiche con sensori di sicurezza*
- *Fotocellula lunghezza busta*
- *Quadro Elettrico con pannello comandi Touch screen, non necessita di aria compressa.*
- *Film utilizzabili: termosaldabili quali polipropilene, politene, micro-perforati, accoppiati etc.*

VELOCITA' DI CONFEZIONAMENTO: FINO A 30 CONFEZIONI AL MINUTO (dipende dal prodotto e dal tipo di film utilizzato)

#### **DIMENSIONI DELLA MACCHINA**

Larghezza: 1200 mm

Lunghezza: 1600 mm

Altezza: 1300 mm